



Aerospace

Fluid Conveyance

Maintaining Aerospace Hose Service Life

The actual service life of a given hose assembly, in a given application, is dependent on many variable factors. These variable factors may include, but are not limited to, operating pressure, pressure surges, flexing, operating temperatures (both fluid and ambient), installed bend radius, cleaning solutions, ozone and assembly routing.

Due to the variety of operating conditions and applications, the user, through their own analysis, testing and/or review of maintenance records and data, is ultimately responsible for making the final selection, or of decisions about replacement hose assemblies and assuring that all performance, safety and warning requirements of the application are met.

Generally speaking, unless otherwise directed by company, user or airline maintenance procedures, OEM maintenance manual instructions, Federal Aviation Administration (FAA) advisory circulars or airworthiness directives or other similar maintenance document(s), it is recommended that hose assembly maintenance and/or replacement be conducted on an "on-condition" basis. However, to provide more clarity in the development of a maintenance approach towards hose assemblies, we offer these additional comments:

We recommend ARP1658* "Visual Inspection Guide for Installed Hose Assemblies" as an aid in conducting inspections of hose assemblies to determine time for replacement.



Hose Assembly applications may be thought of in three general categories:

- Normal Duty
- Moderate or Heavy Duty
- Demanding or Severe Duty

*Society of Automotive Engineers, Aerospace Recommended Practice

Normal Duty Hoses

Typically, these are hose assemblies in less demanding applications, such as in-body, in-wing or other applications not normally exposed to the environment, cleaning fluids, continuous temperature extremes, heavy pressure pulsation, etc., and having infrequent maintenance actions associated with their installation.

Recommended Maintenance Approach: On-Condition



Moderate or Heavy Duty Hoses

Typically, these are hoses exposed to more frequent maintenance activity or major system removal, or hoses occasionally exposed to environmental conditions (e.g., upper wheel well hoses, APU hoses)

Recommended Maintenance Approach: Either On-Condition or based on user data and maintenance records

Demanding or Severe Duty Hoses

Typically, these are hoses continuously or routinely exposed to environmental, cleaning, or other harsh operating variables such as landing gear brake hoses, EDP hoses, etc., and associated with major systems requiring regular removal, repair or overhaul.

Recommended Maintenance Approach: Strongly consider replacement at time of major system overhaul

Eaton Corporation
Fluid Conveyance
300 South East Avenue
Jackson, Michigan 49203-1972
Phone: (517) 787-8121
Fax: (517) 787-5758

Eaton Corporation
Fluid Conveyance
Meadowbrook Road
P.O. Box 819
Toccoa, Georgia 30577-0819
Phone: (706) 779-3351
Fax: (706) 779-2638

Eaton Corporation
Fluid Conveyance
2500 West Argyle Street
P.O. Box 819
Jackson, Michigan
Phone: (517) 787-8121
Fax: (517) 789-4716

Eaton Corporation
Fluid Conveyance
4743 Venture Drive
Ann Arbor, Michigan 48108
Phone: (734) 741-5123
Fax: (734) 741-5333

Eaton GMBH
Fluid Conveyance
Posttack 1026
Carl-Benz-Strasse 9
D-82205 Gilching
Germany
Phone: (49) 810-575-0
Fax: (49) 810-575-27

Eaton S.A.
Fluid Conveyance
Chemin De Pau
64121 Serres-Castet
France
Phone: (33) 559-333-864
Fax: (33) 559-333-865

Eaton Limited
Fluid Conveyance
Broad Ground Road
Lakeside
Redditch
Worcs B98 8YS
England
Phone: (44) 152-751-7555
Fax: (44) 152-751-7556



Aerospace